

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW (DEGREE)			FILTER SIZE [MM]	DIMENSIONS (DxL) (WxHxL) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				

## MANUAL IRIS

### 1/4 FORMAT

QS210(C40206)	2.2	1.0 - C	CS	92.60				36.8x36.3	44	
QS310(C40301)	3	1.0 - C	CS	64.24				36.8x33.8	40	
QS610(C40601)	6	1.0 - C	CS	34.83				36.8x33.8	37	

### 1/3 FORMAT

New TS212A(C70214)	2.8	1.2 - C	CS	71.54	94.28			36.6x36.3	44	
TS320NX(C91665)	3.6	2.0	CS	53.90	72.00			30x8	20	FOR B/W CAMERA
New TS412A(C70409)	4	1.2 - C	CS	49.01	63.21			36.6x33.8	39	
TS820NX(C91666)	8	2.0	CS	23.90	31.40			30x8	18	FOR B/W CAMERA
New TS812A(C70807)	8	1.2 - C	CS	25.06	33.30			36.6x33.8	34	

### 1/2 FORMAT

HS316A(C60305)	3.7	1.6 - C	CS	53.54	71.02	93.65	30.5 P=0.5	32x35.7	34	
HS614B(C60622)	6	1.4 - C	CS	33.86	44.55	57.82	30.5 P=0.5	32x35.7	32	
HS1214D(C61217)	12	1.4 - C	CS	16.55	22.06	29.42	30.5 P=0.5	32x35.7	26	
H416(C60402)	4.2	1.6 - C	C	47.87	64.27	86.77		42x43.5	120	
H612A(C60607)	6	1.2 - C	C	32.97	43.55	56.93	40.5 P=0.5	42x46	125	LOCK SCREW EXTRA
H1212B(C61215)	12	1.2 - 22	C	16.93	22.60	30.18	27.0 P=0.5	30x35.5	67	LOCK SCREW EXTRA

### 2/3, 1 FORMAT

C418DX(C30405)	4.8	1.8 - C	C	41.68	55.11	72.37		40.5x35.5	105	LOCK SCREW EXTRA
B618CX-2(C20612)	6.5	1.8 - C	C	29.94	39.73	52.52		48x42	120	
C814(C30808)	8	1.4 - C	C	25.15	33.31	43.88	40.5 P=0.5	42x58	160	
C815B(C30811)	8.5	1.5 - C	C	24.02	31.87	42.09	40.5 P=0.5	42x40	120	LOCK SCREW EXTRA
B1214D-2(C21211)	12.5	1.4 - C	C	16.21	21.53	28.51	40.5 P=0.5	42x50	135	LOCK SCREW EXTRA
B1218-2(C21212)	12.5	1.8 - C	C	16.48	21.90	29.01	40.5 P=0.5	42x40	95	LOCK SCREW EXTRA
C1614A(C31630)	16	1.4 - 22	C	12.70	16.91	22.48	27.0 P=0.5	30x33	58	LOCK SCREW EXTRA
B2514D(C22525)	25	1.4 - 22	C	8.23	10.97	14.62	27.0 P=0.5	30x37.3	76	LOCK SCREW EXTRA
B2518(C22516)	25	1.8 - C	C	8.23	10.95	14.55	40.5 P=0.5	42x40	87	LOCK SCREW EXTRA
B5014A(C25011)	50	1.4 - C	C	4.13	5.50	7.32	46.0 P=0.75	48x48	180	LOCK SCREW EXTRA
B5018A-3(C25010)	50	1.8 - C	C	4.13	5.50	7.32	40.5 P=0.5	42x52.5	130	LOCK SCREW EXTRA
B7514C(C27509)	75	1.4 - C	C	2.75	3.67	4.90	58.0 P=0.75	62x79	450	LOCK SCREW EXTRA

## MANUAL IRIS FOR MACHINE VISION

### 1/2 FORMAT

New H1214-M(C61232)	12	1.4 - 22	C	16.48	21.88	28.92	27.0 P=0.5	29.5x28.5	55	LOCK SCREW
---------------------	----	----------	---	-------	-------	-------	------------	-----------	----	------------

### 2/3 FORMAT

New C1614-M(C31634)	16	1.4 - 16	C	12.87	17.12	22.72	27.0 P=0.5	29.5x33.2	63	LOCK SCREW
New C2514-M(C32500)	25	1.4 - 16	C	8.23	10.97	14.60	27.0 P=0.5	29.5x32	55	LOCK SCREW
New C5028-M(C35001)	50	2.8 - 22	C	4.12	5.50	7.32	27.0 P=0.5	29.5x34	55	LOCK SCREW

## AUTO-IRIS

### 1/4 FORMAT

QS210E(C40202)	2.2	1.0 - 200	CS	92.60				36.8x43.5x36.3	54	VIDEO & DC IRIS
QS310E(C40300)	3	1.0 - 200	CS	64.24				36.8x43.5x33.8	50	VIDEO & DC IRIS
QS610E(C40600)	6	1.0 - 200	CS	34.83				36.8x43.5x33.8	47	VIDEO & DC IRIS

### 1/3 FORMAT

TS212E(C70210)	2.8	1.2 - 200	CS	71.54	94.28			36.8x43.5x36.3	54	VIDEO & DC IRIS
TS412E(C70406)	4	1.2 - 200	CS	49.01	63.21			36.8x43.5x33.8	49	VIDEO & DC IRIS
TS812LX(C70800)	8	1.2 - 90	CS	24.80	32.60			31.2x40x35.7	39	DC IRIS
TS812E(C70804)	8	1.2 - 200	CS	25.06	33.30			36.8x43.5x33.8	44	VIDEO IRIS


### 1/2 FORMAT

HS316TE(C60310)	3.7	1.6 - 90	CS	53.54	71.02	93.65	34 P=0.5	42.8x47.1x36.5	57	VIDEO & DC IRIS
HS614TE(C60631)	6	1.4 - 90	CS	33.86	44.55	57.82	34 P=0.5	42.8x47.1x36.5	60	VIDEO & DC IRIS
HS1214TE(C61228)	12	1.4 - 90	CS	16.55	22.06	29.42	34 P=0.5	42.8x47.1x36.5	46	VIDEO & DC IRIS
HS316E(C60309)	3.7	1.6 - 300	CS	53.54	71.02	93.65	34 P=0.5	42.8x47.1x36.5	57	VIDEO & DC IRIS
HS614E(C60630)	6	1.4 - 300	CS	33.86	44.55	57.82	34 P=0.5	42.8x47.1x36.5	60	VIDEO & DC IRIS
HS1214E(C61227)	12	1.4 - 300	CS	16.55	22.06	29.42	34 P=0.5	42.8x47.1x36.5	46	VIDEO & DC IRIS
H416E(C60405)	4.2	1.6 - 360	C	47.87	64.27	86.77		46.5x50.5x45	135	VIDEO IRIS
H612E(C60625)	6	1.2 - 360	C	32.97	43.55	56.93	43 P=0.75	46.5x50.5x51.1	130	VIDEO IRIS
H1212E(C61220)	12	1.2 - 360	C	16.93	22.60	30.18	43 P=0.75	46.5x50.5x51.1	130	VIDEO IRIS

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW (DEGREE)			FILTER SIZE [MM]	DIMENSIONS (DxL) (WxHxL) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				





## AUTO-IRIS (CONTINUED)

### 2/3, 1 FORMAT


C418E(C30407)	4.8	1.8 - 360	C	41.68	55.11	72.37		46.5x50.5x37.5	120	VIDEO IRIS
C814E(C30821)	8	1.4 - 360	C	25.10	33.22	43.67	43 P=0.75	46.5x50.5x51.1	140	VIDEO IRIS
B1214E(C21223)	12.5	1.4 - 360	C	16.21	21.53	28.51	43 P=0.75	46.5x50.5x47.5	140	VIDEO IRIS
C1614E(C31632)	16	1.4 - 360	C	12.70	16.91	22.48	43 P=0.75	46.5x50.5x46.7	110	VIDEO IRIS
B2514E(C22527)	25	1.4 - 360	C	8.23	10.97	14.62	43 P=0.75	46.5x50.5x51.8	140	VIDEO IRIS
B5018E(C25018)	50	1.8 - 360	C	4.13	5.50	7.32	49 P=0.75	62x51	230	VIDEO IRIS
B7518E(C27513)	75	1.8 - 360	C	2.76	3.67	4.90	49 P=0.75	62x70.5	300	VIDEO IRIS

## ASPHERICAL, ULTRA-HIGH SPEED AUTO IRIS

### 1/3 FORMAT


TS209E-ASP(C70204)	2.8	0.95 - 180	CS	72.69	98.24			48x53x46.9	140	DC IRIS
TS407E-ASP(C70405)	4	0.75 - 180	CS	48.39	62.55		40.5 P=0.5	48x53x53.1	145	DC IRIS
TS807E-ASP(C70803)	8	0.75 - 180	CS	25.07	33.31		40.5 P=0.5	48x53x46.9	135	DC IRIS

### 1/2 FORMAT


HS308EX-ASP(C60304)	3.8	0.8 - 64	CS	54.20	71.98	95.23		47x56.3	240	VIDEO IRIS
HS607EX-ASP(C60621)	6	0.75 - 64	CS	33.02	43.65	57.19	43 P=0.75	47x59.8	250	VIDEO IRIS
HS1208EX-ASP(C61216)	12	0.8 - 64	CS	16.88	22.61	30.32	43 P=0.75	47x56.3	235	VIDEO IRIS

## MANUAL OVERRIDE (REMOTE-CONTROL IRIS)

### 1/2 FORMAT

H416ER(C60404)	4.2	1.6 - 360	C	47.87	64.27	86.77		46.5x50.5x45	135	
H612ER(C60624)	6	1.2 - 360	C	32.97	43.55	56.93	43 P=0.75	46.5x50.5x51.1	140	
H1212ER(C61219)	12	1.2 - 360	C	16.93	22.60	30.18	43 P=0.75	46.5x50.5x51.1	140	

### 2/3, 1 FORMAT

C418ER(C30406)	4.8	1.8 - 360	C	41.68	55.11	72.37		46.5x50.5x37.5	120	
C814ER(C30820)	8	1.4 - 360	C	25.10	33.22	43.67	43 P=0.75	46.5x50.5x51.1	140	
B1214ER(C21221)	12.5	1.4 - 360	C	16.21	21.53	28.51	43 P=0.75	46.5x50.5x47.5	140	
C1614ER(C31631)	16	1.4 - 360	C	12.70	16.91	22.48	43 P=0.75	46.5x50.5x46.7	110	
B2514ER(C22526)	25	1.4 - 360	C	8.23	10.97	14.62	43 P=0.75	46.5x50.5x51.8	140	
B5018ER(C25017)	50	1.8 - 360	C	4.13	5.50	7.32	49 P=0.75	62x51	210	





## AUTO-IRIS FOR HIGH SENSIVITY CAMERA

### 1 FORMAT





B1214E-2000(C21224)	12.5	1.4 - 2000	C	16.21	21.53	28.51	43 P=0.75	46.5x50.5x47.5	140	VIDEO IRIS
B2514E-2000(C22528)	25	1.4 - 2000	C	8.23	10.97	14.62	43 P=0.75	46.5x50.5x51.8	140	VIDEO IRIS
B5018E-1000(C25019)	50	1.8 - 1000	C	4.13	5.50	7.32	49 P=0.75	62x51	215	VIDEO IRIS
B7518E-1000(C27514)	75	1.8 - 1000	C	2.76	3.67	4.90	49 P=0.75	62x70.5	295	VIDEO IRIS

## MANUAL IRIS & AUTO-IRIS PINHOLE





### 1/3 FORMAT

TS420P(C70404)	4	2.0 - C	CS	51.24	68.47			36.5x65.9	74	MANUAL IRIS
TS420PE(C70403)	4	2.0 - 64	CS	51.24	68.47			36.5x42.3x65.9	79	DC IRIS

### 1/2 FORMAT

HS620P(C60613)	6.2	2.0 - C	CS	32.44	42.82	56.12		29x88.1	67	MANUAL IRIS
H620P(C60612)	6.2	2.0 - C	C	32.44	42.82	56.12		29x83.1	63	MANUAL IRIS
HS620PE(C60627)	6.2	2.0 - 300	CS	32.44	42.82	56.12		39x45.5x88.2	105	VIDEO & DC IRIS
H620PE(C60626)	6.2	2.0 - 300	C	32.44	42.82	56.12		39x45.5x83.2	100	VIDEO & DC IRIS

### 2/3 FORMAT

C934P(C30900)	9	3.4 - 22	C	22.30	29.60	39.11		34x164	175	MANUAL IRIS
C934PL(C30901)	9	3.4 - 22	C	22.30	29.60	39.11			210	R/A, MANUAL IRIS
C934PEX-2(C30904)	9	3.4 - 360	C	22.30	29.60	39.11		46.5x164	235	VIDEO IRIS
C934PLEX-2(C30905)	9	3.4 - 360	C	22.30	29.60	39.11			270	R/A, VIDEO IRIS

# COSMICAR / PENTAX

CERTIFIED ISO 9001 & ISO 14001

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW (DEGREE)			FILTER SIZE [MM]	DIMENSIONS (DxL) (WxHxL) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				

## MANUAL IRIS VARI-FOCAL

### 1/4 FORMAT

QS2V2812(C40207)	2.8 - 5.8	1.2 - C	CS	76.21 - 36.41			30.5 P=0.5	36x43.5	45	
------------------	-----------	---------	----	---------------	--	--	------------	---------	----	--

### 1/3 FORMAT

TS2V214(C70213)	2.8 - 6	1.4 - C	CS	72.46 - 35.15	96.94 - 46.74			36x43.2	47	
New TS2V314A(C70308)	3.5 - 8	1.4 - C	CS	58.74 - 26.55	79.85 - 35.44		30.5 P=0.5	36x43.5	43	
TS2V616(C70612)	6 - 12	1.6 - C	CS	34.92 - 17.21	47.22 - 22.97		30.5 P=0.5	36x43.5	43	

## AUTO-IRIS VARI-FOCAL

### 1/4 FORMAT

QS2V2812E(C40205)	2.8 - 5.8	1.2 - 200	CS	76.21 - 36.41			30.5 P=0.5	40.4x45.7x43.5	57	DC IRIS
-------------------	-----------	-----------	----	---------------	--	--	------------	----------------	----	---------

### 1/3 FORMAT

TS2V114E(C70100)	1.6 - 3.4	1.4 - 64	CS	180 - 64.89	180 - 89.55			38.3x44.7x56.7	140	FISH EYE, DC IRIS
TS2V214E(C70209)	2.8 - 6	1.4 - 200	CS	72.46 - 35.15	96.94 - 46.74			40.4x45.7x43.2	59	VIDEO & DC IRIS
TS2V314E(C70306)	3.5 - 8	1.4 - 200	CS	58.74 - 26.55	79.85 - 35.44		30.5 P=0.5	40.4x45.7x43.5	55	VIDEO & DC IRIS
TS2V616E(C70608)	6 - 12	1.6 - 200	CS	34.92 - 17.21	47.22 - 22.97		30.5 P=0.5	40.4x45.7x43.5	53	VIDEO & DC IRIS

## MANUAL ZOOM

### 1/2 FORMAT

H6Z810(C60812)	8 - 48	1.0 - 22	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	57x95	430	
----------------	--------	----------	---	--------------	--------------	--------------	-----------	-------	-----	--

### 2/3 FORMAT

C6Z1218(C31204)	12.5 - 75	1.8 - 22	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	51x90	320	
-----------------	-----------	----------	---	--------------	--------------	--------------	-----------	-------	-----	--

## MANUAL ZOOM (AUTO-IRIS)

### 1/3 FORMAT

TS6ZE(C70605)	6.3 - 38	1.2 - 512	CS	31.26 - 5.59	41.12 - 7.43		49 P=0.75	57.5x77.8	320	VIDEO & DC IRIS
---------------	----------	-----------	----	--------------	--------------	--	-----------	-----------	-----	-----------------

### 1/2 FORMAT

H6ZBE(C60811)	8 - 48	1.0 - 720	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	69x64x95	465	VIDEO IRIS
---------------	--------	-----------	---	--------------	--------------	--------------	-----------	----------	-----	------------

### 2/3 FORMAT

C6ZE(C31219)*	12.5 - 75	1.8 - 720	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	68x90	385	VIDEO IRIS
---------------	-----------	-----------	---	--------------	--------------	--------------	-----------	-------	-----	------------

## MOTORIZED ZOOM (MOTORIZED IRIS)

### 2/3 FORMAT

C6Z1218M3(C31211)	12.5 - 75	1.8 - C	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	101.5x92.2x94.5	820	
-------------------	-----------	---------	---	--------------	--------------	--------------	-----------	-----------------	-----	--

## MOTORIZED ZOOM (AUTO-IRIS)

### 1/3 FORMAT

TS6ZME(C70600)	6.3 - 38	1.2 - 360	CS	31.26 - 5.59	41.12 - 7.43		49 P=0.75	58x63.5x78	410	VIDEO & DC IRIS
TS10ZME(C70500)*	5.8 - 58	1.2 - 360	CS	33.77 - 3.62	44.07 - 4.78		49 P=0.75	64.6x70.3x85	380	VIDEO & DC IRIS
TS15ZME(C70601)*	6 - 90	1.2 - 720	CS	32.96 - 2.33	43.48 - 3.08		62 P=0.75	78x88.5x119	760	VIDEO & DC IRIS
New TS20ZME(C70900)*	9 - 180	1.2 - 510	CS	22.61 - 1.15	30.28 - 1.53		95 P=1.0	116x135x216	2590	VIDEO & DC IRIS

### 1/2 FORMAT

HS6ZME(C60806)	8 - 48	1.4 - 360	CS	24.81 - 4.39	32.78 - 5.82	42.88 - 7.69	49 P=0.75	58x63.5x78	400	VIDEO & DC IRIS
HS10ZME(C60700)	7.5 - 75	1.4 - 360	CS	26.15 - 2.83	34.52 - 3.75	45.05 - 4.95	58 P=0.75	67x75x112	580	VIDEO & DC IRIS
H6ZBME(C60809)*	8 - 48	1.0 - 720	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	64x74.5x97	530	VIDEO IRIS
H10ZME(C60701)*	7.5 - 75	1.2 - 512	C	26.45 - 2.84	34.94 - 3.77	45.63 - 4.99	62 P=0.75	70x80.5x121.5	715	VIDEO IRIS
H15ZME(C60817)*	8 - 120	1.6 - 1000	C	24.76 - 1.76	32.85 - 2.34	43.37 - 3.09	62 P=0.75	78x88.5x134	800	VIDEO IRIS
H20ZME(C61221)*	12 - 240	1.6 - 720	C	17.17 - 0.88	22.95 - 1.17	30.78 - 1.56	95 P=1.0	116x135x216	2590	VIDEO IRIS


### 2/3, 1 FORMAT

C6ZAME(C31220)*	12.5 - 75	1.8 - 720	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	101.5x92.2x94.5	620	VIDEO IRIS
C10ZAME(C31002)*	10.5 - 105	1.4 - 1000	C	18.97 - 2.02	25.24 - 2.68	33.49 - 3.56	72 P=0.75	121x109.5x149.5	1380	VIDEO IRIS
C14ZME(C31009)*	10 - 140	1.9 - 720	C	19.89 - 1.52	26.41 - 2.02	34.96 - 2.68	86 P=1.0	128x118.6x165	2000	VIDEO IRIS
B12ZCME(C21517)*	15 - 180	1.9 - 1400	C	13.29 - 1.18	17.69 - 1.57	23.54 - 2.09	107 P=1.0	145x137.5x227	3070	VIDEO IRIS

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW (DEGREE)			FILTER SIZE [MM]	DIMENSIONS (D×L) (W×H×L) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				




## ■ MOTORIZED ZOOM (PRE-SET/MOTORIZED IRIS)

### 1/3 FORMAT

TS10ZM-P(C70505)	5.8 - 58	1.2 - 22	CS	33.77 - 3.62	44.07 - 4.78		49 P=0.75	72x76x86	430	
------------------	----------	----------	----	--------------	--------------	---	-----------	----------	-----	--

## ■ MOTORIZED ZOOM (PRE-SET/AUTO-IRIS)

### 1/3 FORMAT

TS10ZME-P(C70501)*	5.8 - 58	1.2 - 360	CS	33.77 - 3.62	44.07 - 4.78		49 P=0.75	64.6x70.3x85	430	VIDEO & DC IRIS
TS15ZME-P(C70604)*	6 - 90	1.2 - 720	CS	32.96 - 2.33	43.48 - 3.08		62 P=0.75	78x88.5x119	770	VIDEO & DC IRIS
New TS20ZME-P(C70903)*	9 - 180	1.2 - 510	CS	22.61 - 1.15	30.28 - 1.53		95 P=1.0	116x135x216	2630	VIDEO & DC IRIS

### 1/2 FORMAT

H6ZBME-P(C60810)*	8 - 48	1.0 - 720	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	64x74.5x97	540	VIDEO IRIS
H10ZME-P(C60702)*	7.5 - 75	1.2 - 512	C	26.45 - 2.84	34.94 - 3.77	45.63 - 4.99	62 P=0.75	70x80.5x121.5	740	VIDEO IRIS
H15ZME-P(C60820)*	8 - 120	1.6 - 1000	C	24.76 - 1.76	32.85 - 2.34	43.37 - 3.09	62 P=0.75	78x88.5x134	810	VIDEO IRIS
H20ZME-P(C61224)*	12 - 240	1.6 - 720	C	17.17 - 0.88	22.95 - 1.17	30.78 - 1.56	95 P=1.0	116x135x216	2620	VIDEO IRIS

### 2/3, 1 FORMAT

C6ZME-P(C31221)	12.5 - 75	1.8 - 720	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	101.5x92.2x94.5	655	VIDEO IRIS
C10ZAME-P(C31003)*	10.5 - 105	1.4 - 1000	C	18.97 - 2.02	25.24 - 2.68	33.49 - 3.56	72 P=0.75	121x109.5x149.5	1420	VIDEO IRIS
C10ZAME-PI(C31006)	10.5 - 105	1.6 - 1000	C	19.11 - 2.02	25.38 - 2.68	33.61 - 3.55	72 P=0.75	121x109.5x153	1430	VIDEO IRIS
C14ZME-P(C31010)*	10 - 140	1.9 - 720	C	19.89 - 1.52	26.41 - 2.02	34.96 - 2.68	86 P=1.0	128x118.6x165	2040	VIDEO IRIS
B12ZCME-P(C21520)*	15 - 180	1.9 - 1400	C	13.29 - 1.18	17.69 - 1.57	23.54 - 2.09	107 P=1.0	145x137.5x227	3150	VIDEO IRIS

## ■ MOTORIZED ZOOM LENS (PRE-SET/AUTO-IRIS & MANUAL OVERRIDE)

MANUAL OVERRIDE OPTION IS AVAILABLE ON THE MODELS ASTERISKED (\*)

ITEM	MODEL NUMBER	REMARKS
2xEXTENDER	2-EX(C80001)	Rear conversion lens to double the focal length.
	S2-EX(C80034)	[2-EX: For C-Mount lenses, S2-EX: For CS-Mount lenses]
MACRO-FOCUS RING	EX-C6(C90100)	6 different length of rings to adjust the focal point for the close-up application
	RR-27(C80036)	Reverse ring to mount lenses in reverse on cameras for the close-up application
	RR-40.5(C80037)	Especially recommended where magnification of 1x or more is required
WIDE ATTACHMENT	WA-2(C80027)	Front attachment lens to widen the angle of view without reducing the aperture ratio [WA-2: H612E, C814E, B1214E]
	WA-5(C80033)	[WA-5: HS316TE, HS316E, HS614TE, HS614E, HS1214TE, HS1214E]
MOUNT ADAPTER	PC-MOUNT(C80018)	Adapter for Pentax P-Mount lens to be used with C-Mount camera
	KC-MOUNT(C80020)	Adapter for Pentax K-Mount lens to be used with C-Mount camera
DUMMY LENS	DM-163(C80029)	Dummy camera lens
	DM-E01(C80040)	[DM-163: Manual iris type, DM-E01: Auto-iris type]
FILTER		Various kinds of optical filters and accessories are available